

SURE FLAME®

SAFE. TOUGH. RELIABLE.

SE410

DUAL FUEL/DIRECT
ENCLOSED FLAME
400,000 BTU



SE410 400,000 BTU / Hr



Features:

- Innovative enclosed flame design
- Ductable up to 75 feet
- Digital display with real-time diagnostics
- Oxygen sensor to ensure clean combustion
- Easy access to interior components
- 1 HP motor for increased airflow
- Smart design – stackable and easy to move
- 3 Year Warranty[†]

Specifications

Heat Input	Approx. Fuel Consumption	Fan Rating	Motor Power	Heat Rise	
400,000 BTU / Hr	16.5 L / Hr (propane) 18.5 Lbs / Hr (natural gas) 400 CFH	4500 CFM*	120V / 7.5A / 1 Ph	95°C	
Outlet Diameter	Max. Duct Length	Dimensions (LxWxH)	Weight	Gas Connection	Gas Supply Pressure
16" or 2 x 12"	75'	56" x 24.5" x 32.5"	250 Lb	1" NPT	1/2 PSI

*Advertised CFM is the fan rating, not the output CFM. Actual CFM output will vary depending on operating conditions. [†]See sureflame.ca/warranty for coverage.

SUREFLAME.CA
1-800-661-1162