

INDIRECT HEATERS

SAFE. TOUGH. RELIABLE.







ROBUST PERFORMANCE

Our patented wave exchanger design provides 30% more surface area to heat than flat panels. Using powerful fans and a unique cross flow air exchange, more heat is extracted from the panels so it ends up in your duct — not out the stack.

SIMPLE CONTROLS, ADVANCED FEATURES

Simple doesn't have to be low tech. Our new cold-rated keypad features large easy-to-read color-coded start / stop buttons.

Advanced diagnostics are also available if needed and easily viewed through the bright OLED display.

DURABLE AND RELIABLE

Sure Flame heaters are built to last, featuring tough steel bodies, high quality components, and durable powder coated paint. Our experienced team specializes in manufacturing products of the highest quality.



INDIRECT MODELS

| | IX410 | 1X800 | IX1500 | ID400 | 1D800 | ID800T | SFT800 |
|----------------------------|-----------------|----------------------|---------------------------------|-----------------|----------------------|----------------------|---------------------|
| | LPG/NG | LPG/NG | LPG/NG | DIESEL | DIESEL | DIESEL | DIESEL |
| Output (BTU/hr) | 400,000 | 800,000 | 1,500,000 | 400,000 | 800,000 | 800,000 | 800,000 |
| Efficiency | 84% | 86% | 82% | 84% | 86% | 86% | 86% |
| Heat Rise | 101°C | 80°C | 95°C | 101°C | 80°C | 80°C | 80°C |
| Fan Rating (CFM) | 5,000 | 13,600 | 20,500 | 4,300 | 13,600 | 13,600 | 13,600 |
| Heated Air Flow (CFM) | 2,300 @110°C | 7,000 @82°C | 10,000 @82°C | 2,300 @110°C | 7,000 @82°C | 7,000 @82°C | 7,000 @82°C |
| Max Static Pressure | 3.2 | 5 | 5.4 | 2.4 | 5 | 5 | 5 |
| Max Discharge Temp. | 116°C | 100°C | 116°C | 116°C | 100°C | 100°C | 100°C |
| Max Duct Length (ft) | 100 | 200 | 400 | 100 | 200 | 200 | 200 |
| Recirculation | YES | YES | YES | YES | YES | YES | YES |
| Outlet (inches) | 2x12, 1x16 | 2x16, 1x20 | 2x20, 1x24 4x16 | 2x12, 2x16 | 2x16, 1x20 | 2x16, 1x20 | 2x16, 1x20 |
| Voltage | 120V 1Ph | 208/230V 1 or 3Ph | 208/230V, 460V 575V-3Ph Only | 120V 1Ph | 208/230V 1 or 3Ph | 208/230V 1 or 3Ph | 12kW Generator |
| Dimensions (LWH-inches) | 82.5x29x58 | 95x29x58 | 125x32.5x77.5 | 85x32x59 | 95x33x56 | 95x33x76 (w/tank) | 156x100x97 |
| Weight (lbs) | 560 | 1340 | 2160 | 662 | 1260 | 2100 (w/tank) | 5214 (7300 full) |

^{* 100}k, 200k, 300k BTU Indirect models (diesel) also available. See page 7 for more details.







IX1500

- LPG/NG
- X 1,500,000 BTU
- 20,500 CFM
- 400 FT MAX DUCT





- Exceptional reliability and performance
- New OLED screen displays heater diagnostics
- Powerful 10 HP fan motor for high CFM
- Compact design takes up less space
- Low NOx version available (special order only)



When big heat is needed, the IX1500 is sure to impress. Featuring Sure Flame's patented burner and exchanger technology, the IX1500 leads the industry in performance and reliability.

IX800

- ♠ LPG/NG
- ₩ 800,000 BTU
- 🔀 13,600 CFM
- 200 FT MAX DUCT





- Compact design, only 29 inches wide
- Parallel inlet/outlet design for easy recirculation
- 86% efficient in a wide range of air excess
- 7.5 HP fan motor allows long duct runs
- New OLED screen displays heater diagnostics



The IX800 packs a punch. Our most advanced design delivers with huge CFM and efficiency, all in a tight and compact design. Get all the heat you expect with the IX800.

IX410



- LPG/NG
- 400,000 BTU 💥
 - 5,000 CFM 🔀
- 100 FT MAX DUCT



- Exceptional reliability and performance
- Impressive heat rise of 101°C
- Whisper quiet operation
- High efficiency saves on fuel
- Operates on standard 120V outlet

0

Get more heat and use less fuel with the IX410. Sure Flame's patented combustion technology delivers a difference you can feel. The IX410 outperform all other heaters in this category.

ID800T



DIESEL

800,000 BTU 13,600 CFM

200 FT MAX DUCT





- Excellent start-up in cold weather
- Reliable Tiger Loop fuel aeration
- Standard pre-heated oil filter
- 1 or 3 phase power compatibility
- Available with or without 443L fuel tank



The ID800T is rock solid. Unbeatable uptime along with great real-world efficiency make this diesel indirect hard to beat. Proven reliable start-ups in even the coldest climates.





Featuring our rock-solid ID800 platform, the SFT800 is proven ultra-reliable even in the harshest of climates including the Northern Alberta oil sands. Outstanding uptime and amazing heat output.





If you need more heat out of your diesel 400, the ID400 may be your solution. With Sure Flame's exclusive combustion technology, this heater will impress with its efficiency and heat rise.

ID300



- 300,000 BTU 💥
 - 2,530 CFM 🔀
- 75 FT MAX DUCT

- Simple to operate
- Standard pre-heated fuel filter
- 16 hrs of run time per tank (134L)
- Operates on 120V outlet
- Convenient fuel level indicator



The ID300 is a great, cost-effective solution when reliable dry heat is the goal. This medium duty indirect features a preheated fuel filter, simple controls, and a large integrated fuel tank.



ID100

100,000 BTU

1,020 CFM

25 FT MAX DUCT



- Simple to operate
- 21 hrs of run time per tank (65L)
- Electronic flame control
- Operates on 120V outlet
- Convenient fuel level indicator





Like the ID300, the ID100 is a cost-effective solution when reliable dry heat is the goal. This small duty indirect features a preheated fuel filter, simple controls, and a large integrated fuel tank.

DIRECT HEATERS

Sure Flame has been manufacturing direct fired heaters for almost 60 years! When used properly, direct fired heaters are a safe, reliable, and very cost effective solution to your heating project. All Sure Flame heaters are CSA certified and test-fired to ensure maximum safety and performance.







BUILT TO LAST

Sure Flame heaters are built tough, featuring solid steel bodies, durable powder coated paint, and the best components available.

EXCEPTIONAL PERFORMANCE


Direct fired heaters are nearly 100% efficient, giving you the most heat for your money. Sure Flame directs have stood the test of time and are still the benchmark.

SIMPLE & RELIABLE

Sure Flame heaters are easy to operate and maintain. These heaters are renowned for their reliability and keep going year after year.



SE410



The efficiency of a direct fired heater combined with the safety of an indirect. The SE410 direct can be safely ducted up to 50 feet, all while keeping discharge air completely safe.

HOW A DUCTABLE DIRECT WORKS



^{*} The SE410 can also be safely operated indoors with proper ventilation. Always follow the local and national gas code(s). Refer to product manual for more details.

S2200D

- ♠ LPG/NG
- × 2,250,000 BTU
- X 12,000 CFM
- 40 FT MAX DUCT





- Great for make-up air applications
- Ductable up to 40 feet (metal ducting)
- High efficiency impeller fan
- 1 or 3 phase power options
- Easy to read OLED display



The S2200D delivers a whopping 2.25 million BTU's and includes a 12,000 CFM rated fan, ductability of up to 40 ft, and a new cold-rated OLED display for real-time diagnostics.

S1500E

- ♠ LPG/NG
- 1,500,000 BTU
- 3,000 CFM





- 2 stage High / Low operation for maximum efficiency
- Standard remote thermostat
- Low amp draw
- Stackable design
- High quality paint




Designed to withstand the rigours of an active jobsite, the S1500E features include a 2-stage gas valve (Hi/Lo), low amp electrical system, stackable design, and a remote thermostat.

SURE FLAME

SL11E

- LPG/NG
- 1,000,000 BTU



- Legendary Sure Flame reliability
- Optional remote thermostat
- Low amp draw
- Stackable design
- High quality paint





The SL11E had similar features as the SL11E but is rated at 1 million BTU's (single stage only). The S1500E does not come standard with a remote thermostat (available as an option).






Safe, simple, and ultra-reliable, the S400T is the standard in this category. High quality manufacturing by an experienced team means this heater will perform for years to come.

S150

- ♠ LPG
- X 1,500 CFM





- No electricity required
- Includes regulator, POL, and 15 ft. hose
- Heavy duty steel body
- Optional bolt-on fan available (FN2)



The S150 comes standard with a regulator, POL fitting, and 15 feet of quality hose. For even better performance, add the FN2 bolt-on fan (1500 CFM). Power is required for the FN2.

S100

- LPG/NG
- 💢 100,000 BTU
- X 1,500 CFM





- Durable all steel construction
- Light weight and portable
- Convenient carrying handle
- Quick change fuel selector (LPG/NG)
- Very quiet operation



The most compact dual fuel (NG/Propane) heater available. The S100 is super quiet and easy to move around with a convenient carrying handle right on the top.

ST3 TORCH

90,000 - 375,000 BTU 💥



- Durable steel head
- Ergonomic design
- Hand-built in Canada
- Superior quality and performance





Manufactured from high-quality components, this torch is great for many tasks on the job site, on the farm, or at home. Available with 10 feet of high-quality (CGA approved) hose, POL valve, and regulator.

ST2 TORCH

50,000 - 200,000 BTU 💥





- Ergonomic design
- Hand-built in Canada
- Superior quality and performance







The ST2 is slightly smaller than the ST3 and uses less fuel -- a great choice if higher BTUs are not needed. Available with 10 feet of high-quality (CGA approved) hose, POL valve, and regulator.

FN42C

14,000 CFM 42" FAN BLADE





- Heavy duty steel shell
- Adjustable airflow settings (tilt)
- Built-in lifting hook
- Large pneumatic wheels
- All parts replaceable and stocked



The FN42C is built Sure Flame tough. Perfect on the job site or in the shop, this heavy-duty fan is a workhorse designed to give you years of trouble-free service.

FN20C

5,000 CFM 20" FAN BLADE





- Built to last decades
- Heavy duty steel shell
- Stackable design
- All parts replaceable and stocked
- High quality paint



Tired of cheap, throwaway plastic fans? Sure Flame's FN20C is the epitome of a quality, long-lasting product. Hand-built in Canada by experienced professionals.

UB12E



4,700 CFM 🔀 12" FAN BLADE



- Explosion-proof blower / exhauster
- CSA approved for Class 1, Group D hazardous locations
- Ductable on both ends (12" diameter)
- Built in handles for easy relocation
- Durable steel shell

Stackable design

High quality motor and components



The UB12E is great for use in confined spaces or anywhere that flammable gases or vapors are a concern. Does NOT come with a plug on the cord and needs to be wired by a certified professional.



_

